

Report from tests No 3/BU/00

RESULTS of TESTS

Note: the results of the tests are the integral part of the report from tests No 3/BU/00 which cannot be used in fragments without a permission from the Institute of Naphta Technology

Name of a sample supplied by the customer: Petromix

The results:

	Subject of tests	Unit	Heavy residual fuel oil No"3"	Heavy residual fuel oil No „3” + Petromix in ratio: 1:10000	Base light fuel oil	Base light fuel oil + Petromix In ratio: 1:10000	Method of testing acc. to
1.	Kinematic viscosity at 80°C	mm ² /s	94.00+/-0,35	92.66+/-0,35	-	-	PN-81/C-0401
2.	Corrosion on steel pins	corossion degree	after 1 h – no corossion after 6 h – no corossion after 24 h – heavy corossion of „D” degree	after 1 h – no corossion after 6 h – no corossion after 24 h – heavy corossion of „C” degree	-	-	ASTM D 665A Estimation acc to NACE TM 02-75
3.	Interfacial tension water-oil	mN/m	-	-	29.25+/-2%	10.6+/-2%	PN-90/C-04809

- a) heavy fuel oil „3” acc to PN-76/C-96024
- b) base light fuel oil acc to PN-C-96024

Date of tests beginning: 09.05.2000

Date of tests termination: 31.05.2000

Additional pieces of information:

The report was performed on:
31.05.2000

Origin: EUDistributor: „ORMET”, ul. Sadowa 12 ; 43-100 Tychy ; PolandTel/fax: +48-32-3230564 ; www.ormet.com.pl ; e-mail: ormetbw@gmail.com